

Oak Foundation



Foundation is our entry-level engineered oak flooring range, designed for efficiency with reliable performance.

Its slimmer construction optimises heat transfer, making it particularly suitable for use with modern underfloor heating systems. The range features seven colours, some in rustic oak with a planed finish, others in extra-rustic oak with a brushed finish for more surface texture.



Autumn



Basalt



Dune



Leaf



Night



River



Spring

Planks: From £99m²

Widths available: 180mm, 220mm

Thickness available: 13mm

Duplex engineered timber

Herringbone: £114m²

Herringbone: 120 x 600mm

Thickness available: 13mm

Duplex engineered timber

Prices do not include VAT or delivery

Technical Specifications

SPECIES	European oak
APPLICATION	Commercial and residential (Indoor)
CONSTRUCTION	Duplex engineered 4mm top layer oak
BEVEL	Micro bevel as standard
INSTALLATION TECHNIQUE	Nail, glue bonding or floating
SUITABLE FOR UFH	Yes, when duplex engineered
FIRE CLASSIFICATION	EN: 13501: Dfl-S1
THERMAL CONDUCTIVITY	0.119-0.17 λ W/mK
HARDNESS	4,982 N (Janka)

Timber floors are easy to care for, please call us for further information on the best way to look after your floor.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.