

# Oak Landmark

---



By using a planer, rather than sanding the oak, the Landmark grain is torn open creating a distinctive, lively appearance in the surface of the floor.

This refined collection has many bespoke options and an array of colours achieved by a combination of smoking, specialist treatments, and the application of pigmented oils.

Available in boards up to an impressive 280mm width, various parquets and opulent panels, this collection gives you the opportunity to create your own unique floor.



Ascott



Saltram



Wakehurst



Stourhead



Tyntesfield



Osterley



Dyrham



Tredegar



Standon



Dalton



Compton



Gunby



Derrymore



Stoneacre



Knowle



Tatton



Montacute

### **Planks: From £114 sqm**

Widths available: 140mm, 180mm, 220mm, 240mm, 260mm, 280mm

Thickness available: 15mm, 20mm

Solid or duplex engineered

Brushed texture or reclaimed finish also available

### **Herringbone & Chevron: From £144 sqm**

Herringbone: 90 x 540mm, 90 x 810mm, 120 x 600mm, 140 x 700mm, 160 x 800mm, 180mm x 900mm

Chevron: 120 x 600mm, 140 x 700mm, 180 x 900mm

Thickness available: 15mm

Duplex engineered

Brushed texture or reclaimed finish also available

### **Parquet Panels: From £179 sqm**

Ten Patterns available in set sizes

Thickness available: 20mm

Solid or duplex engineered

Reclaimed finish as standard

Prices do not include VAT or delivery

## Technical Specifications

<b>SPECIES</b>	European oak
<b>APPLICATION</b>	Commercial and residential (Indoor)
<b>CONSTRUCTION</b>	Duplex engineered 4 or 6mm top layer oak Solid oak
<b>BEVEL</b>	Micro Bevel as standard, also available hand scraped or square edged
<b>INSTALLATION TECHNIQUE</b>	Nail, glue bonding or floating
<b>SUITABLE FOR UFH</b>	Yes, when duplex engineered
<b>FIRE CLASSIFICATION</b>	EN: 13501: Dfl-S1
<b>THERMAL CONDUCTIVITY</b>	0.119-0.17 $\lambda$ W/mK
<b>HARDNESS</b>	4,982 N (Janka)

Timber floors are easy to care for, please call us for further information on the best way to look after your floor.

Timber is a living material. A wooden floor, although no longer growing as part of a tree, is still very much part of its environment. As such, it responds to the light, temperature, humidity and wear to which it is exposed.

As the floor ages the colour of the wood will mellow and change. This is a natural process that occurs as the surface of the wood is exposed to oxygen in the air and to ultraviolet light from the sun. Painted surfaces, upholstery, furniture and rugs all undergo this same process over time.

After a number of years you may wish to have the floor surface sanded down and re-finished. You could then choose to re-oil the floor or have it stained first or even re-finished in lacquer.



West:  
61 Paddington St  
London W1U 4JD  
020 7486 4838

East:  
7a Ezra Street  
London E2 7RH  
020 7221 8188

Registered in England & Wales: Solid Floor Ltd. 7a Ezra Street, London E2 7RH  
Company Reg No: 03287805 | VAT Reg No: 710 4793 50  
FSC® licence: C117337 | FSC COC: CU-COC-828136 | PEFC COC: CU-PEFC-82813  
solidfloor.co.uk sales@solidfloor.co.uk  solidfloor  solidfloor